How to access the clusters

The DCSR maintains a general purpose cluster (Curnagl) which is described here. Researchers needing to process sensitive data must use the air gapped cluster Urblauna which has replaced Jura.

There are several requirements to be able to connect to the clusters:

1. Have a UNIL account
2. To be part of a PI project
3. To be on the UNIL or CHUV network (either physically or using the UNIL VPN if you work remotely)
4. To have a SSH client

Step 0: Have a UNIL account

This applies to members of the CHUV community as well as for external collaborators

See the documentation for how to get a UNIL account

CHUV users should also consult https://www.unil.ch/ci/ui/ext-hosp for more information.

Step 1: Be part of a PI project

To access the clusters, your PI will first need to request resources via: https://requests.dcsr.unil.ch . Then the PI must add you as a member of one of his project. Within 24 hours your access should be granted.

Step 2: Activate the UNIL VPN

Unless you are physically within the UNIL network you need to activate the UNIL VPN (Crypto). Documentation to install and run it can be found here.

Step 3: Open a SSH client

On Linux and Mac environments, a SSH client should be available by default. You simply need to open a terminal.

Windows users can either use PowerShell if they are on Windows 10, or install a third party client such as PuTTy or MobaXterm.

Step 4: Log into the cluster

Curnagl

```
ssh -X <username>@curnagl.dcsr.unil.ch
```

where `<username>` is your UNIL username name. You will have to enter your UNIL password.

Note: we strongly recommend you to establish SSH keys to connect to the clusters and to protect your SSH keys with a passphrase.

More details are available regarding the different clients in this documentation.

Urblauna

See the Urblauna documentation

Créé 2021-05-21 08:08:58 UTC par Etienne Orliac
Mis à jour 2026-09-16 15:34:11 UTC par PW