

MATLAB on the clusters

The full version of MATLAB is only installed on the login and interactive nodes so in order to run MATLAB jobs on the cluster you first need to compile your .m files then run them using the MATLAB runtime.

This is because the UNIL has a limited number of licences and with an HPC cluster it's easy to use them all.

The number of licences and available toolboxes is detailed [here](#)

Thankfully the compilation process isn't too complicated but there are a number of steps to follow and a few issues to be aware of.

Let's start with our MatrixCAB.m file

```
disp("Matrix A:");  
A = [1, 2; 3, 4];  
disp(A);  
  
disp("Matrix B:");  
B = [5, 6; 7, 8];  
disp(B);  
  
disp("Matrix C = A * B:");  
C = A * B;  
disp(C);
```

First of all we need to load the module that provides MATLAB

```
[ulambda@login ~]$ module load matlab  
[ulambda@login ~]$ module list  
  
Currently Loaded Modules:  
  1) matlab/2021b
```

We now compile the MatrixCAB.m file with the `mcc` compiler which is now in the path.

```
$ mcc -v -m MatrixCAB.m
```

```
Compiler version: 8.1 (R2021b)
```

```
Dependency analysis by REQUIREMENTS.
```

```
Parsing file "/users/ulambda/MatrixCAB.m"
```

```
[(referenced from command line).
```

```
Generating file "/users/ulambda/readme.txt".
```

```
Generating file "MatrixCAB.sh".
```

The compiler documentation can be found at <https://ch.mathworks.com/help/compiler/mcc.html>

Note that there are now 3 new files:

```
readme.txt
```

```
run_MatrixCAB.sh
```

```
MatrixCAB
```

If we take a look at the last file we see that it's an executable file

```
$ file MatrixCAB
```

```
MatrixCAB: ELF 64-bit LSB executable, x86-64, version 1 (SYSV), dynamically linked (uses shared libs), for GNU/Linux 2.6.32, BuildID[sha1]=ad76a4654419e7968208a77a172f103afe2d77c2, stripped
```

The curious are welcome to look at the output from `ldd` which shows what the executable is linked to.

```
$ module load matlab-runtime
```

```
$ ldd MatrixCAB
```

The `readme.txt` explains in great detail how to run the compiled object and the `run_MatrixCAB.sh` script is for launching the job.

In order to make use of the executable we need to load the MATLAB runtime environment module

```
module load matlab-runtime
```

Please note that the runtime has to correspond to the version of `mcc` used to compile the `.m` file. Please see the following page for the corresponding runtime and compiler versions:

<https://ch.mathworks.com/products/compiler/matlab-runtime.html>

On the DCSR clusters the modules are configured to have the same version naming scheme:

```
matlab-runtime/2021b  
matlab/2021b
```

The runtime module sets the `MCR_PATH` variable which is needed by the `run_MatrixCAB.sh` script.

To launch the compiled MatrixCAB object we need to put all the elements together:

```
sh run_MatrixCAB.sh $MCR_PATH
```

Obviously this should be done on a compute node using a job script:

```
#!/bin/bash  
  
#SBATCH --time 00-00:05:00  
#SBATCH --cpus-per-task 1  
#SBATCH --mem 4000M  
  
module load matlab-runtime/2021b  
  
MATLAB_SCRIPT=MatrixCAB  
  
sh run_$MATLAB_SCRIPT.sh $MCR_PATH  
  
echo "Finished - next time I'll port my code to Julia"
```

Task farming with Matlab

When processing numerous Matlab jobs in parallel on the clusters, you will likely encounter stability issues with some jobs failing randomly, other hanging (see below the explanations from Matlab support). To solve the issue, you must set the `MCR_CACHE_ROOT` environment variable (see https://ch.mathworks.com/help/compiler_sdk/ml_code/mcr-component-cache-and-ctf-archive-embedding.html) in order that the same location (by default in your home directory) is not used by all jobs.

For job arrays, you can adopt the following:

```
#!/bin/bash
```

```
#SBATCH --array=1-5
#SBATCH --partition cpu
#SBATCH --mem=8G
#SBATCH --time=00:15:00

module load matlab-runtime/2021b

# Create a task-specific MCR_CACHE_ROOT directory

mcr_cache_root=/tmp/$USER/MCR_CACHE_ROOT_${SLURM_ARRAY_JOB_ID}_${SLURM_ARRAY_TASK_ID}
mkdir -pv $mcr_cache_root
export MCR_CACHE_ROOT=$mcr_cache_root

### YOUR MATLAB ANALYSIS HERE

MATLAB_SCRIPT=MatrixCAB

sh run_${MATLAB_SCRIPT}.sh $MCR_PATH

###

# Tidy up the place
rm -rv $mcr_cache_root
```

Explanations from Matlab support

“ When running a MATLAB Compiler standalone executable, the MCR_CACHE_ROOT location is used by the standalone executable to extract the [deployable archive](#) into. As the name suggests, the extracted archive is cached in this location, meaning the archive is extracted the very first time you run the application and then for consecutive runs the already extracted data from the cache is used.

There are mechanisms in place which try to ensure that when you run multiple instances of the same application at the same time, you do not run into any concurrency issues with this cache (e.g. a second instance should not also try to extract the archive if the first instance was already in the process of doing this).

However, there are some limitations to these mechanisms; they were designed to deal with concurrency issues which might occur if an interactive user would run a handful of concurrent instances of the application; when doing this interactively this implies that you are not starting all those instances at exactly the same point in time and there are at least a few seconds between starting each instance. If you are somehow starting *a lot* of instances at *virtual the same time* (through some shell script, or possible even some cluster scheduler), this mechanism may break down. The likelihood of running into issues increases even more if the cache is located on a shared network drive, shared by multiple machines (which can definitely be the case for a home directory), and all these machines are running instances of the same application.

This is probably what you are running into then. Giving each instance its own cache location would prevent those issues altogether as there would be no concurrency in the first place.

Révision #6

Créé 20 mai 2021 08:40:02 par Ewan Roche

Mis à jour 7 juin 2024 08:23:37 par Cristian Ruiz